



Global Barrier Services

Slipcoat IRC™ Application Instructions

Architectural/Decorative Concrete

1. Equipment

- * Manual, pump-up type sprayer or spray can. Product may also be wiped on using a soft cloth for smooth application.
- * Use fan type spray tip(s)

2. Product

Make sure the **Slipcoat IRC™** product is at least 60° - 70°F (16° - 22°C) or higher for optimal viscosity.

3. Application

- * Make sure that the surfaces that the **Slipcoat IRC™** will be applied to are clean and free of any pre-existing concrete buildup and/or residue.
- * It is important that the application surfaces are as dry as possible.
- * **Slipcoat IRC™** does not require any dilution for use.

DO NOT dilute or cut with any other product.

- * Apply **Slipcoat IRC™** using a spray system or something similar that will evenly apply the product in a light coating. A fan shaped pattern is recommended. **Slipcoat IRC™** can also be wiped onto surfaces using a soft cloth. Take care not to over-apply.

- * Spray a thin coat of **Slipcoat IRC™** onto all the surfaces where buildup or sticking occurs. Make sure to keep the application light. There should be little to no dripping or pooling of the **Slipcoat IRC™** product.

IMPORTANT

- * **DO NOT** apply to walkways, ladders, steps, hand-rails or any other surface/area that it may pose a slip hazard
- * **DO NOT** apply to lights, windows or other glass/translucent surfaces
- * Be aware of and clean up any overspray or spilled product
- * Clean up of the **Slipcoat IRC™** product can be done using warm, soapy water or by using a cleaner such as **Simple Green**.

STORAGE OF THE SLIPCOAT IRC™ PRODUCT

- * Store the **Slipcoat IRC™** product in a protected area at or above 60° F.
- * Store the spray wand and pump equipment in a protected area where it will not be damaged or collect dirt/debris in the spray tip.

Product Support Contact Information:

Global Barrier Services, Inc.
1001 Avenida Pico, Suite C-433, San Clemente, CA 92673

Tel. 949 542 7440
Email. info@globalbarrierservices.com