


Slipcoat™ IRC™

All Purpose Industrial Non-Stick Coating



Nothing Sticks to Us





**USDA
CERTIFIED
BIOBASED
PRODUCT**
PRODUCT 99%

Slipcoat™ IRC™

SLIPCOAT™ IRC™ is an all-purpose, industrial non-stick coating that is designed for use across a wide variety of industries. SLIPCOAT™ IRC™ is designed to prevent the buildup of mud, ice, clay, asphalt, concrete, waste products and other materials on equipment surfaces.

PRODUCT OVERVIEW:

- 99.8% biodegradable, environmentally friendly
- 100% made in the USA and certified USDA Bio-Preferred
- Reduces/eliminates build-up caused by sticking and/or freezing
- Has no negative effect on painted surfaces
- Available in convenient 15 oz. spray cans
- Does not evaporate at high temperatures or freeze at low temperatures
- Non-hazardous, non-toxic and no harmful fumes or vapors
- Advanced filming technology allows for low usage requirement – about 1 gallon per 800 - 1,000 square feet
- Provides a protective film that helps to inhibit rust and corrosion and increase lubricity
- * Opportunity to reduce cleaning times, reduce wear & tear and increase equipment lifespan



Slipcoat™ IRC™

IS DESIGNED FOR USE ON VIRTUALLY ANY HARD SURFACE AND IN ANY APPLICATION WHERE STICKING AND/OR FREEZING OF MATERIALS OCCURS

Slipcoat™ IRC™ is designed to be used on any surface where sticking and/or freezing is an issue, including but not limited to:

- Mud
- Clay
- Modified Asphalt
- Compost
- Biosolids
- Concrete
- Waste Materials
- Agricultural
- Snow
- Ice
- Dirt
- Any other material that sticks or freezes

FREQUENTLY ASKED QUESTIONS

What is SLIPCOAT™ IRC™?

SLIPCOAT™ IRC™ is a 100% environmentally friendly, 99.8% biodegradable, **USDA BioPreferred**, non-stick coating product. It reduces or eliminates materials build-up on surfaces caused by sticking and/or freezing, protects against rust and corrosion, increases lubricity and increases equipment lifespan

Can SLIPCOAT™ IRC™ be applied indoors and in confined spaces?

Yes, SLIPCOAT™ IRC™ is non-toxic, non-hazardous and has no harmful fumes or vapors.

How much SLIPCOAT™ IRC™ is needed for a given surface area and how often does it need to be applied?

Application rate is typically about 1 gallon per 800 - 1,000 square feet of surface area. Application frequency will vary depending upon the application.

Will SLIPCOAT™ IRC™ damage paint?

No, SLIPCOAT™ IRC™ will not have any effect on painted surfaces.

Does SLIPCOAT™ IRC™ contain any carcinogens or reproductive hazards?

No. SLIPCOAT™ IRC™ is manufactured following strict health, safety and environmental guidelines.

Will SLIPCOAT™ IRC™ work under extreme winter conditions?

Yes, SLIPCOAT™ IRC™ has been proven effective in temperatures exceeding -40°F.

How can I get started with SLIPCOAT™ IRC™?

Please visit our storefront at www.slipcoats.com or our website at www.globalbarrierservices.com. You can also contact us at info@globalbarrierservices.com or by telephone at (949) 542-7440 for more

THE BUILD-UP SOLUTION



Global Barrier Services, Inc.

1001 Avenida Pico, Suite C-433,
San Clemente, California 92673
Tel. 949 542 7440

info@globalbarrierservices.com

www.slipcoats.com

www.globalbarrierservices.com

